

PMR-12V320W1AT

Delta Panel Mount 12/26/7A, PFC, Low profile, forced cooling



ELECTRICAL SPECIFICATION

Product Type	Power supply, Industrial Power Supply, LED Driver
Output Voltage	12V DC
Rated Current	26.7A
Power (W)	320
Dimming	No
AC input voltage range	Universal
PFC	Yes
Protection class	I
Inrush Current (typ.)	50A
IP protection level	IP20
Over Current / Overload protection	Type: hiccup mode, auto-recovery.
Over Current / Overload protection (range)	110-175%
Over Voltage protection (range)	13.2-16.8V
Over Voltage protection	Type: shut down output voltage. Re-power on to recovery.
Over Temperature protection	Type: shut down output voltage. Re-power on to recovery.
Safety Standards	EN 62368-1 :2014+A11 :2017, Compliance to EN62368-1
EMC Emission	Compliance to EN55032, EN55032, Compliance to EN61000-3-3
EMC Immunity	EN61000-4-2, -3, -4, -5, -6, -8, -11, TÜV EN 55035:2017 + A11:2020, EN 61000-4-4, EN 61000-4-6, EN 61000-4-3, EN 61000-4-5
Harmonic Current	EN61000-3-3, Compliance to EN61000-3-3
Weight (kg)	0.643

Warranty	5 years
Mounting	surface

MECHANICAL SPECIFICATION