

DRC-48V060W1RZ

Delta DIN Rail 48V/1.25A, Chrome II



- Features:
- Class II, Double Isolation (No Earth connection is required)
 - Supports universal AC input voltage and DC input voltage
 - Mechanical dimensions are designed to meet DIN 43880 for building automation
 - Low no load power consumption and compliance with DOE VI efficiency standard
 - NEC Class 2 / Limited Power Source (LPS) certified
 - Over Voltage Category III

ELECTRICAL SPECIFICATION

Product Type	Industrial Power Supply, DIN Rail Power Supply, Power supply
Output Voltage	48V DC
Rated Current	1.25A
Power (W)	60
Dimming	No
AC input voltage range	Universal
Protection class	II
Inrush Current (typ.)	40A
IP protection level	IP20
Over Current / Overload protection	Type: auto-recovery.
Over Current / Overload protection (range)	105~150%
Over Temperature protection	Type: shut down output voltage. Re-power on to recovery.
Over Voltage protection	Close output, recovers automatically after fault removed
Over Voltage protection (range)	< 68V
EMC Emission	EN55032, EN61000-3-2, EN61000-3-3
EMC Immunity	EN61000-4-2, -3, -4, -5, -6, -8, -11
Harmonic Current	EN61000-3-2, Compliance to EN61000-3-3, EN61000-3-3
Weight (kg)	0.17
Warranty	5 years

Mounting	DIN
Programmable	No

MECHANICAL SPECIFICATION